



Model PC-545(Y)
File Number: E194560



COMPANY

ZHEN JIANG CHI MEI CHEMICAL CO LTD
No.88, Hanqiao Road, Zhenjiang New Area
ZHENJIANG, Jiangsu Sheng 212132 China

MODEL INFO

WONDERLOY: PC-545(Y)
Polycarbonate/Acrylonitrile Butadiene Styrene (PC/ABS), furnished as pellets
(Y) – Optional suffix; may be suffixed with one or two alphabet but except H, unconcerned with formula or constituent changed.

FLAMMABILITY PROPERTIES	额定值	测试方法
Flammability		ANSI/UL 94
1.2 mm, Color: ALL	V-0	
1.5 mm, Color: ALL	V-0	
2.5 mm, Color: ALL	5VA V-0	
3.0 mm, Color: ALL	5VA V-0	
ISO/IEC FLAMMABILITY PROPERTIES	额定值	测试方法
Flammability		IEC 60695-11-10
1.2 mm, Color: ALL	V-0	
1.5 mm, Color: ALL	V-0	
2.5 mm, Color: ALL	V-0	
3.0 mm, Color: ALL	V-0	
Flammability		IEC 60695-11-20
2.5 mm, Color: ALL	5VA	
3.0 mm, Color: ALL	5VA	

Glow Wire Ignition Temperature (GWIT)		IEC 60695-2-13
1.5 mm	800 °C	
3.0 mm	800 °C	
Glow Wire Flammability Index (GWFI)		IEC 60695-2-12
1.5 mm	960 °C	
3.0 mm	960 °C	
ELECTRICAL PROPERTIES		
	额定值	测试方法
Hot-wire Ignition (HWI)		UL 746A
1.2 mm	PLC 4	
1.5 mm	PLC 4	
2.5 mm	PLC 4	
3.0 mm	PLC 4	
High Amp Arc Ignition (HAI)		UL 746A
1.2 mm	PLC 2	
1.5 mm	PLC 2	
2.5 mm	PLC 2	
3.0 mm	PLC 2	
Comparative Tracking Index (CTI)		UL 746A
Dielectric Strength		ASTM D149
High Voltage Arc Tracking Rate (HVTR)		
Volume Resistivity		ASTM D257/IEC 60093
High Voltage, Low Current Arc Resistance		
THERMAL PROPERTIES		
	额定值	测试方法
Relative Thermal Index - Electrical Strength		UL 746B
1.2 mm	60 °C	
1.5 mm	95 °C	
2.5 mm	95 °C	
3.0 mm	95 °C	

Relative Thermal Index - Mechanical Impact		UL 746B
1.2 mm	60 °C	
1.5 mm	90 °C	
2.5 mm	90 °C	
3.0 mm	90 °C	
Relative Thermal Index - Mechanical Strength		UL 746B
1.2 mm	60 °C	
1.5 mm	95 °C	
2.5 mm	95 °C	
3.0 mm	95 °C	
Ball Pressure Temperature		110 °C
PHYSICAL PROPERTIES		
	额定值	测试方法
Dimensional Change	0.0 %	ASTM D1042/ISO 2796

Report Date: 2021-01-13
Revision Date: 2021-01-13

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过UL认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明： "©2024 UL LLC."